



B6

PIPES, FITTINGS &amp; FLOW CONTROL

PRODUCT

# Ductile Iron (DI) Fittings

DN 80 to DN 2000, PN10 to PN25



## OVERVIEW

Ductile Iron (DI) Fittings are essential pipeline components used to connect, divert, reduce, branch, and terminate piping systems, ensuring strong, durable, and leak-proof performance.

## SPECIFICATIONS

|                  |                                                                          |
|------------------|--------------------------------------------------------------------------|
| SIZES            | DN 80 mm to DN 2000 mm                                                   |
| PRESSURE RATINGS | PN10, PN16, PN25, and project-specific pressure ratings                  |
| JOINT SYSTEMS    | Push-On (Tyton) · Flanged · Mechanical · Restrained                      |
| COATINGS         | Cement Mortar · Zinc · Bituminous · Epoxy · FBE · PU protective coatings |

## FITTING TYPES

DI Bends · DI Tees · DI Reducers · DI Couplings · DI Dismantling Joints · DI Flanged Adaptors · DI End Caps  
DI Repair Clamps · Other Specialized Fittings

## APPLICATIONS

Potable Water Supply · Sewerage · Irrigation · Industrial Piping · Municipal Infrastructure

## KEY FEATURES

- Excellent mechanical strength
- Corrosion resistance
- Long service life
- Leak-proof performance

### Enquire — DI Fittings

WhatsApp +977 9852033007 · kediawaterhouse@gmail.com · Stocked in Biratnagar, supplied across Nepal